

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ :
E02B 3/10, E02D 17/18, 19/18

A1

(11) International Publication Number: WO 00/34587

(43) International Publication Date: 15 June 2000 (15.06.00)

(21) International Application Number: PCT/EP99/09534

(22) International Filing Date: 6 December 1999 (06.12.99)

(30) Priority Data:
MI98A002658 10 December 1998 (10.12.98) IT

(71) Applicant (for all designated States except US): SIBELON
S.R.L. [IT/IT]; Via Monte Bianco, 5, I-28041 Arona (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SCUERO, Alberto [IT/CH];
Piazza Molino Nuovo, 5, CH-6900 Lugano (CH).


(74) Agent: COLOBERTI, Luigi; Via E. De Amicis, 25, I-20123
Milan (IT).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG,
BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB,
GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK,
MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU,
ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL,
SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ,
MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE,
DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE),
OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML,
MR, NE, SN, TD, TG).

Published*With international search report.*

*Before the expiration of the time limit for amending the
claims and to be republished in the event of the receipt of
amendments.*

(54) Title: EMBANKMENT DAM AND WATERPROOFING METHOD



(57) Abstract

The dam comprises a body (11) made of loose material, for example earth and/or rocks (A), and a water barrier (12) axially extending to the dam body (11), comprising a waterproofing layered membrane (13) and a zone of waterpermeable loose material (B), on at least one side of the membrane (13), which can be injected with a sealing fluid and is designed to avoid puncturing of the membrane (13) and to allow the monitoring of the leakage waters due to failures in the waterproofing membrane (13). The water barrier (12) can be provided inside the dam body or close to the upstream face.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | | | |
|----|--------------------------|----|--|----|--|----|--------------------------|
| AL | Albania | ES | Spain | LS | Lesotho | SI | Slovenia |
| AM | Armenia | FI | Finland | LT | Lithuania | SK | Slovakia |
| AT | Austria | FR | France | LU | Luxembourg | SN | Senegal |
| AU | Australia | GA | Gabon | LV | Latvia | SZ | Swaziland |
| AZ | Azerbaijan | GB | United Kingdom | MC | Monaco | TD | Chad |
| BA | Bosnia and Herzegovina | GE | Georgia | MD | Republic of Moldova | TG | Togo |
| BB | Barbados | GH | Ghana | MG | Madagascar | TJ | Tajikistan |
| BE | Belgium | GN | Guinea | MK | The former Yugoslav Republic of Macedonia | TM | Turkmenistan |
| BF | Burkina Faso | GR | Greece | ML | Mali | TR | Turkey |
| BG | Bulgaria | HU | Hungary | MN | Mongolia | TT | Trinidad and Tobago |
| BJ | Benin | IE | Ireland | MR | Mauritania | UA | Ukraine |
| BR | Brazil | IL | Israel | MW | Malawi | UG | Uganda |
| BY | Belarus | IS | Iceland | MX | Mexico | US | United States of America |
| CA | Canada | IT | Italy | NE | Niger | UZ | Uzbekistan |
| CF | Central African Republic | JP | Japan | NL | Netherlands | VN | Viet Nam |
| CG | Congo | KE | Kenya | NO | Norway | YU | Yugoslavia |
| CH | Switzerland | KG | Kyrgyzstan | NZ | New Zealand | ZW | Zimbabwe |
| CI | Côte d'Ivoire | KP | Democratic People's Republic of Korea | PL | Poland | | |
| CM | Cameroon | KR | Republic of Korea | PT | Portugal | | |
| CN | China | KZ | Kazakstan | RO | Romania | | |
| CU | Cuba | LC | Saint Lucia | RU | Russian Federation | | |
| CZ | Czech Republic | LI | Liechtenstein | SD | Sudan | | |
| DE | Germany | LK | Sri Lanka | SE | Sweden | | |
| DK | Denmark | LR | Liberia | SG | Singapore | | |
| EE | Estonia | | | | | | |

EMBANKMENT DAM AND WATERPROOFING METHOD

SCOPE OF INVENTION

This invention refers to embankment dams, and to an improved method for their construction and waterproofing.

5. STATE OF THE ART

Water resources become more and more precious and their conservation is becoming more and more important; therefore it is essential to search for and adopt solutions which minimise the waste of water and which allow a clever management of the existing water resources.

The most ancient typology of a dam is the embankment dam, obtained by using natural materials available on site for the creation of embankments capable of contrasting the pressure exerted by the water collected in the natural reservoir delimited by the dam itself. The dam body must be statically stable and at the same time it must avoid water leakage caused by possible infiltration, which would cause a decrease of the quantity of water resource available, and which could also jeopardise the stability or the safety factor of the dam itself. As a matter of fact, uncontrolled water infiltration into the dam body can cause undesirable interstitial pressures, erosion phenomena and the formation of preferential flows or of "piping" capable of causing even the collapse of the whole structure.

25. In many cases earthfill and/or rockfill dams are preferred to conventional concrete dams, to roller compacted concrete (RCC) dams, to masonry dams or other, as they are less expensive; therefore it is important to build embankment

dams which have a high safety factor and are watertight.

During the years different techniques have been developed to make embankment dams watertight. There are substantially two tendencies for the waterproofing of embankment dams:

5. the first one consists in waterproofing the upstream face, and the second one consists in creating a waterproofing core inside the body of the dam itself.

- The waterproofing of the upstream face stops possible infiltration onto the dam surface next to the water impounded in the reservoir. The waterproofing barrier is executed on the slopes of the dam body and is therefore subject to stresses and deformations which occur over time in the dam body. This kind of barrier must therefore have good characteristics of elasticity and at the same time of watertightness.
- 10.
 - 15.

In general this kind of barrier consists of an upstream face built in concrete, with waterproofing joints, waterstops in synthetic material and/or copper, or with facings made of a bituminous concrete.

20. In both cases the deformations which the dam body undergoes during exploitation are such as to cause possible failures in these waterproofing barriers with subsequent water loss and risk for the stability of the structure.

- Recently, watertight upstream facings have been executed with flexible synthetic geomembranes, capable of granting the watertightness of the dam and at the same time capable of sustaining strong deformations, even concentrated, without damage.
- 25.

Geomembranes simply laid over the upstream face of the dam,

however, need ballasting layers in order to avoid that the geomembrane itself can be displaced or damaged by the suction exerted by winds, or by the fatigue caused by the action of waves.

5. A second solution which has been widely adopted in construction of embankment dams foresees the construction of a central watertight core, made with natural materials positioned so as to grant low permeability, lower than 1×10^{-10} cm/sec, for example clay or bentonite, placed during construction of the embankment. In the latest decades, the central core has also been constructed in bituminous concrete and in conglomerates cement-bentonite based.

15. All the above-mentioned solutions have emphasised some constructive difficulties, as well as a rather high probability not to be able to reach the required reliability, besides the impossibility of checking the extent of their efficiency by measuring the occurring seepage. Furthermore, should infiltration or water leakage through the central core occur, the repair is extremely difficult and brings uncertain results.

25. Hence, for the construction of embankment dams, the need of finding new construction and waterproofing solutions which, by using artificial materials, allow to obtain an effective watertightness for the whole life of the dam, by using systems and materials which can be coupled with aggregates of the dam body capable of granting only the static function, and which are also easily and economically constructed, whose efficiency can be checked over time and which, in case of damage, can be simply and efficiently repaired.
- 30.

OBJECTS OF THE INVENTION

The main object of this invention is to execute an embankment dam and a construction and waterproofing method, which can reach the above-mentioned objectives, allowing to make consistent savings on the total cost of construction of the dam.

5.

In particular, an object of this invention is to supply a method for the construction and the waterproofing of an embankment dam which uses a watertight barrier capable of adapting to any deformation of the dam body without losing its efficiency or its watertightness.

10.

A further object of this invention is to supply an embankment dam and a construction and waterproofing method which allow to adopt suitable monitoring systems of the watertightness of the waterproofing barrier, and which at the same time allow to intervene for the necessary repairs, or to execute waterproofing connections with other rigid structures of the dam itself.

15.

Another object of this invention is to supply a method for the construction and the waterproofing of an embankment dam which allows to use an upstream waterproofing system comprising a proper flexible synthetic geomembrane extending from the crest to the upstream toe of the dam, allowing a non-rigid connection of the geomembrane itself, capable of following the deformations, sometimes high, of the dam body itself which can occur over time.

20.

25.

A further object of this invention is to supply a method for the construction and the waterproofing of an embankment dam which allows to immediately use the dam, even if not yet finished, during its construction.

30.

BRIEF DESCRIPTION OF THE INVENTION

- According to this invention, a method has been provided for the construction and the waterproofing of a dam comprising an embankment body in coarse loose material having a longitudinal axis, in which the aforementioned dam body is made by superimposing layers of earth and/or rocks, with a water barrier which develops from the bottom towards the top and which extends along the longitudinal axis of the dam body, characterised by steps of performing a the water barrier including at least one synthetic and elastically yieldable waterproofing membrane, and at least one transition zone of selected loose material, on at least one side of the membrane, said loose material having a high permeability to water and to the injection, if necessary, of fluid or fluidised sealing materials, performing the transition zone between the waterproofing membrane and the dam body during the construction by superimposed layers of the coarse material of the dam body; and by supplying anchoring means for anchoring the waterproofing membrane to the dam body and to the foundation during the construction of the dam.

- According to a first particular aspect of the invention a method has been provided for the construction and the waterproofing of dams for retaining water in a reservoir, in which the dam comprises a body in coarse loose material, made by superimposed layers in earth and/or rock or similar, to provide a static function of resistance to the thrust impounded by the water in the reservoir, the method comprising the steps of performing a central core defining a water-barrier in selected fine loose material, from sand to gravel, with a high permeability, higher than the dam body, for instance comprised between 1×10^{-1} and 1×10^{-5} cm/sec; this barrier incorporates at least a waterproofing

- membrane in an elastically yieldable synthetic material, extending from the dam body foundation to the crest, and longitudinally to the dam itself. At least one side of the waterproofing membrane is covered by at least one layer of
5. synthetic material, for example a geotextile, capable of protecting the membrane against the mechanical aggression of the inert loose materials of the central core; the waterproofing membrane and the protecting layer in synthetic material being progressively incorporated in the
10. different superimposed layers in loose material, during the construction of the dam body and of the central core.

- According to another aspect of the invention, a method has been provided for the construction and the waterproofing of dams designed for retaining water in a reservoir, in which
15. the dam comprises a body in coarse loose material, made of superimposed and compacted layers in earth and/or rock or similar, and a waterproofing membrane in an elastically yieldable synthetic material, extending from the dam body foundation to the crest, and longitudinally on an upstream
20. face of the dam, the waterproofing membrane being fastened by means of strips of said elastically yieldable synthetic material, previously embedded between superimposed layers of loose material of said body of the dam, and successively welded to the waterproofing membrane during the
25. construction and the installation on the above-mentioned upstream face.

- According to a particular aspect of the invention, the waterproofing membrane is built on the upstream face of the dam already completed, by adjoining several sheets in
30. synthetic material which are unrolled from the top to the bottom of the dam and welded to the anchoring strips embedded in the dam body during its construction.

- According to another particular aspect of the invention, the waterproofing membrane is built on the upstream face of the dam by adjoining several sheets in synthetic material which are laid horizontally in respect to the longitudinal axis of the dam and welded to anchoring strips in synthetic material embedded in the dam body during the construction of the dam itself. This solution is particularly advantageous if compared to the previous ones because it allows an anticipate, although partial use of the dam, during its construction, without having to wait for the long time normally required for the stabilisation and testing of the dam after completion.

- In the solution with the waterproofing membrane laid directly on the upstream face of the dam, the use of a waterproofing synthetic material, flexible and elastically extensible, coupled and adherent to a substrate in synthetic material, such as a geotextile or similar, besides supplying a mechanical protection against any accidental puncturing of the waterproofing membrane by the loose material of the dam, supplies also surface with a high friction coefficient. This surface with high friction coefficient allows to maintain in their position the single sheets of the membrane during their installation, even if they are not yet welded to the anchoring strips.

- The connection between the anchoring strips and the waterproofing membrane can be executed by thermo-welding in accordance with specific methods further explained, by using in any case for the waterproofing membrane and for the anchoring strips, synthetic materials that are chemically compatible for their heat-welding.

According to one more aspect of the invention, the lower edge of the waterproofing membrane is fastened to the dam

body's upstream toe by creating a longitudinal bend which allows the membrane itself to better adapt to possible movements of the dam body.

For the scope of this invention the various words used have the meaning herein defined:

5.

geomembrane: flexible synthetic material with two prevailing dimensions, characterised by a low permeability to fluids;

10.

geocomposite: flexible synthetic material with two prevailing dimensions, made by coupling, during production, of two or more layers of synthetic materials with different characteristics and functions, one of which consists of a geomembrane having a waterproofing function;

15.

geosynthetic: synthetic material with two prevailing dimensions; which depending on its characteristic can have different functions such as waterproofing, antipuncturing protection, sliding, etc.;

geotextile: synthetic material consisting of textile fibres, with high permeability;

20.

layered membrane: consists of at least two layers of synthetic materials with two prevailing dimensions, having different functions, which can be coupled during manufacturing or can be only superimposed during the construction of the dam.

25.

BRIEF DESCRIPTION OF THE DRAWINGS

These and further characteristics and advantages of the method for construction of embankment dams, as well as of

the waterproofing system, will better result from the following description of some examples of preferential embodiments.

In the drawings:

- 5. - Fig. 1 is a front view of a generic dam, part of which has been realised in loose material according to a first type of realisation of an embankment dam having a central waterproofing core according to this invention;
- Fig. 2 is a section according to line 2-2 of figure 1;
- 10. - Fig. 3 is a section according to line 3-3 of figure 2;
- Fig. 4 is an enlarged detail of figure 3;
- Fig. 5 is an enlarged detail of figure 2;
- Fig. 6 is an enlarged detail of a second type of an embankment dam having a central waterproofing core;
- 15. - Fig. 7 is a cross-sectional view according to line 7-7 of figure 6;
- Fig. 8 is a schematic view of a scaffolding which can be used for the construction of an embankment dam according to the example of figure 6;
- 20. - Figg. 9 and 10 show some significant constructional phases of an embankment dam having a central core with a double waterproofing layered membrane, according to the example of figure 6;
- Figg. from 11 to 14 show some significant constructional phases of an embankment dam with a central core having a double layered membrane according to an alternative embodiment of the invention.
- 25. - Fig. 15 shows a first way of constructing a waterproofing barrier according to the invention in correspondence of the upstream face;
- 30. - Fig. 16 shows part of a front view of the waterproofing layered membrane on the upstream face of the dam of figure 15;

- Fig. 17 shows an enlarged detail of figure 15;
- Fig. 18 shows a second way of constructing a waterproofing barrier next to the upstream face;
- Fig. 19 shows an enlarged details of figure 18;
- 5. - Fig. 20 shows part of a front view of the waterproofing layered membrane on the upstream face of the dam of the previous figures;
- Fig. 21 shows an enlarged detail of an anchoring system at the lower edge of the waterproofing layered membrane;
- 10. - Fig. 22 is an enlarged detail of fig. 21.

DETAILED DESCRIPTION OF THE INVENTION

Central waterproofing layered membrane

- With reference to figures from 1 to 5 we will describe at first the conceptual scheme and the general construction principles of an embankment dam with a central waterproofing layered membrane, according to the invention.
- 15.

- Figure 1 shows an example of a generic dam which includes a part 10 for instance in concrete, consisting instance in a spillway, an intake tower or other, and a part 11 in coarse loose material, comprises an upstream dam body 11A and a downstream dam body 11'A in earth and/or rock, and a water-barrier including a central core 12 in fine loose material suitably selected to constitute a proper transition layer, having characteristics of permeability and injectability which will be further explained; the core 12 in the example under consideration has been made waterproof by means of a layered membrane 13 consisting of a "package" of geosynthetics, which extends in the direction of the longitudinal axis of the dam, starting from a concrete beam 16 for the anchorage to the foundation of the dam body 11, towards the top, up to the crest, the layered membrane thus
- 20.
- 25.
- 30.

being incorporated in the mass of loose material which forms the central core 12.

5. In particular, as shown in the detail of figure 4, the waterproofing package 13 is substantially composed of a geomembrane 14 in synthetic, waterproofing, flexible and elastically yieldable material, for example in PVC or PE or PP of adequate thickness, and of two lateral protective substrates 15, one on each side, in synthetic material, for example a geotextile, in order to avoid any accidental
10. puncturing of the waterproofing geomembrane and hence a loss of watertightness of the membrane 13 itself.

As shown in the above-mentioned figures, according to this first embodiment of the invention, a central core of the waterproofing barrier is constructed, placed vertically or
15. inclined, in fine or granular loose material B, adequately selected, preferably monogranular, incorporating a waterproofing package 13 in synthetic material. This material has adequate flexibility and elasticity characteristics, to follow and/or compensate movements of
20. the dam body 11A, 11'A which may occur over time, without failure; package 13 at the dam upstream toe is fastened to a concrete beam 16 or otherwise connected to the foundation.

Therefore, as shown in the sectional view of figure 3, the
25. waterproofing package 13 is disposed inside or between two side by side arranged and vertically extending zones constituting the central core 12; these two zones are covered with the different layers A of coarse loose material composing the dam body, placed both on the
30. upstream side and the downstream side of the artificial waterproofing barrier thus constructed.

According to the scheme of the above-mentioned figures, package 13 has the primary function of waterproofing and watertightness, while the loose material B of core 12 has a transition and, if necessary, a drainage function. On the contrary, the natural or inert material A constituting the body 11A and 11'A of the dam, has the sole static function of resisting to the thrust impounded by the water in the upstream reservoir.

During construction as well as during operation of the dam, the central waterproofing layer 14 of package 13 is therefore protected on both sides, the upstream side and the downstream side, by one or more substrates 15 of flexible synthetic material, such as geotextile or similar. The aim is to favour the distribution of the hydrostatic pressures which act on the dam body itself and which are transmitted to core 12 as well, as well as to reduce the effect of the mechanical aggression, by puncturing and/or abrasion, exerted by inert materials on the geomembrane of the water barrier, as previously discussed.

Layer 15 of protection synthetic material can be independent from internal layer 14 (geomembrane) or can be hot-coupled to it like a sandwich. The waterproofing layered membrane consisting of layer 14 and of protecting geotextiles 15 is therefore in contact with a layer of adequately selected fine loose material, for instance granular material, such as sand, stony material such as gravel or similar, with dimensions ranging between 3 mm and 30 mm approximately. The dimensions of the loose material can be greater and even reach 10 cm, according to the requirements for transition and drainage of the central core; even if it is not necessary, it is generally preferred that material B of the transition area of core 12 is a monogranular material or, e.g., it may be requested

that the selected material which forms the downstream zone of the central core has a high degree of permeability to fluids, comprised approx. between about 1×10^{-1} and 1×10^{-5} cm/sec in order to allow, if needed, efficient drainage of the water which could seep through cracks or local failure of geomembrane 14.

Therefore the combination of the selected material B of core 12, of geotextiles 15 and geomembrane 14 allows to create an effective waterproofing and at the same time an optimal transfer of the static loads from body 11A to body 11'A of the dam, through core 12, while at the same time constructing an effective coupling of the various separation interfaces between material A which forms body 11A, 11'A of the dam, generally consisting of earth and/or rock, and the selected stony material B constituting central core 12.

As previously mentioned, at the dam bottom along the entire foundation line, package 13 is watertightly and intimately connected to a concrete beam 16, or a similar anchoring mean, from which a waterproofing screen 16' departs towards the underlying soil; this waterproofing screen is executed for example by means of grouting with concrete or resins or similar and more generally by plastic diaphragms.

The perimeter beam 16 can be independent or be part of an inspection gallery (not shown) placed at the dam base, in axis with central core 12.

The fundamental reason for the presence of the foundation beam or of other equivalent structure is to have an anchoring element for the geomembrane, and a connection between the waterproofing barriers over and under the foundation plan.

Behind package 13, on the downstream side, starting from layer B in fine selected material of central core 12, at the bottom of central core 12, in correspondence of beam 16, it is possible to create a drainage pipe system. The system consists of pipes 17 which are inclined towards the dam's downstream side and are able to collect any water infiltration through cracks or failure of package 13 which can consequently be monitored.

The drained waters can be conveyed to one or more collecting points 17' where they are monitored by means of proper devices and successively discharged downstream.

The above-mentioned system provides the following advantages:

- 1) It creates a continuous artificial waterproofing barrier, in flexible synthetic material, which extends from the foundation to the crest of the dam body. The waterproofing barrier can continue to reach the deep layers of the ground by means of screen 16', executed by grouting or with suitable plastic diaphragms, which departs from the foundation beam 16 which thus constitutes the connecting element;
- 2) It constructs a watertight core, able to follow the dam body's deformations which occur over time due to the settlement which the dam body itself undergoes due to its own weight and to the hydrostatic load, keeping the waterproofing and deformability characteristics of the waterproofing core unaltered over time;
- 3) it verifies the efficiency of the waterproofing system by means of the monitoring system placed downstream of the central core itself.

Connection with rigid structures

5. In some situations, as schematically represented in figure 1, it may occur that body 11A, 11'A of the embankment dam, with waterproofing core 12 and package 13, are in contact with rigid parts of the dam itself, for example executed in conventional concrete, in roller compacted concrete (RCC), in masonry or other.

10. This situation occurs when only a part of the dam is built in loose material, while the other part is a gravity dam executed with conventional techniques. The same situation occurs also when an intake tower, executed in concrete or masonry, is inserted in the body of the embankment dam.

15. In these cases, it is necessary to achieve the continuity of the waterproofing between package 13 of the central core of the embankment dam, subject to greater deformations, and the part of structure 10, more rigid, subject to smaller deformations.

20. For this purpose, as schematically shown in figure 5, the connection of the waterproofing package 13 to the rigid body 10 of the dam can be made by means of one or more strips 18 consisting of bands 18' of supplementary layered membranes, of the same material as package 13, installed vertically like in a bellows-shape, adherent to the rigid body 10 as shown. A vertical edge of the bellows-shaped package 18 is watertight anchored to the rigid body of the dam by means of mechanical fastening devices, schematically shown, e.g. by means of metal profiles which fasten by compression the edge of strip 18 folded in a bellows-shape against the rigid body 10, to which the profiles are fastened by means of bolts and washers 20, while the other vertical edge of strip 18 is heat-welded to the

25.

30.

- correspondent opposite edge of package 13. Strip 18 will thus form a kind of bellows-shaped folds, like in a bellows. The folds are executed by welding geomembrane bands 18' according to the "joined-hands" scheme, or by
5. folding a membrane strip on itself. This bellows-shaped folded element which faces the dam body 11A, 11'A in loose material, is left free to move or to follow the deformations which the dam can be subjected to over time.

- The connection between package 13 of the central core and
10. the strip of layered, bellows-shaped membrane 18, can be executed directly or by means of supplementary elastic strips suitably shaped with extra material, and made of the same material as package 13.

- The bellows can be protected on its sides by further
15. elastic strips. Strips 18' of the bellows, made of the same material as package 13, are properly shaped or welded in the "joined-hands" configuration, with extra material, so that they can form further supplementary deformable bellows.

- Between the bellows' strips made of layered membrane, and above them, other layers of material 19 can be placed, which reduce the friction and therefore facilitate the relative sliding (geotextile, synthetic liners, layers of silicon, of Teflon, sand, etc.), and which supply a further
20. protection to the bellows.
- 25.

- The settlement of dam body 11A, 11'A in loose material will therefore produce stresses in the contact surface between body 11A, 11'A and the rigid body 10; in this zone the bellows-shaped layered membrane is installed, which, due to
30. its geometric shape and to the elastic characteristics of the material with which it has been made, will allow to

follow this settlement.

Practically body 11A, 11'A in loose material settles, causing a correspondent lowering of the elevations of the different layers of the package of the layered membrane 13 contained in the central core 12. Since package 13 is connected to the external edge of the strip of the bellows-shaped layered membrane 18, also this one will be compelled to go down according to the settlement of body 11A, 11'A of the dam. The internal edge of the bellows-shaped membrane 18 is on the contrary rigidly connected to the rigid part 10 of the dam, as previously described. Therefore, the variation in position between the internal edge which remains fixed, and the external edge which goes down, will be absorbed partly by the folds of bellows 18, partly by the supplementary connection strips, if present, as well as by the minimum rotation of the bands of the bellows itself and by the elasticity of the material which package 13 is made of.

The described solution is such that, while the fill constituting body 11A and 11'A of the embankment dam settles, package 13 can freely follow such settlements while keeping the waterproofing connection with the rigid structure 10.

In certain situations it would even be possible to avoid the use of the bellows-shaped membrane 18, as the settlement of body 11A, 11'A in loose material normally occurs in an almost homogeneous and linear way; therefore, the supplementary elastic strips alone could provide a high safety coefficient by coping with the induced deformation and the resulting stress, since package 13 and the bellows strips 18, which are able to undergo elongation at break which can reach 200% and more, contribute to absorb the

deformations and the stresses.

Central double waterproofing membrane

- Figures 1-5 show the use of a single package 13 as a waterproofing element of the central core 12; other solutions are nevertheless possible, one of which is shown in figures 6 and 7 of the attached drawings.
- 5.

- As shown in these figures, in order to increase the safety and waterproofing degree of the central core 12, it is possible to install two adjoining packages 131 and 132 in impermeable synthetic and elastically yieldable material, perfectly identical to package 13. The two packages are at a suitable distance one from the other, and are positioned parallel to the longitudinal axis of the dam, from the base of the body in loose material 11A, 11'A, to the crest of the dam.
- 10.
- 15.

In this case, the central core 12 in selected loose material includes an intermediate zone 121 placed in the gap between the two packages 131 and 132, and two lateral confinement zones 122, 123.

- 20.
- The intermediate zone 121 thus created must have a grading suitable to allow the injection, if necessary, of fluid or fluidised substances for the sealing of leakage, such as bentonite sludge or other, capable of locally creating or restoring watertightness in case of puncturing or failure of package 131.
- 25.

Also in this case, both packages 131 and 132 are placed inside a fine or granular material selected, from sand to gravely, as previously shown, and are protected on both faces by a layer of flexible synthetic material 15, of

geotextile type, with an anti-puncturing and anti-grip function.

5. The selected material of the zone 121 between the two packages 131, 132 must allow an adequate transfer of the loads from one side of the dam body to the other one and must always have a high degree of injectability for the foreseen scopes, creating a homogeneous static body.

10. Also in this case the two packages 131 and 132 are fastened to the dam perimeter, on the foundation, with a watertight mechanical anchorage. Again, from the concrete perimeter beam 16 or similar can depart a waterproofing screen 16' executed by grouting or by plastic diaphragms, as previously mentioned.

15. In general, the fine selected material of zone 121 placed between the two membranes, and if necessary the fine selected material of the two lateral zones 122 and 123, can be of the same type B previously described for the central core 12 of the example of figure 1, namely it must have a high degree of injectability and draining capacity; yet, 20. according to the requirements, it is possible to use selected materials B and C with different draining characteristics for the three zones 121, 122 and 123 of the central core, as shown in figure 6.

25. The example of figure 7 shows another variant which is possible if the configuration with the two packages 131 and 132 is adopted.

30. As shown in figure 7, the two packages, the upstream one 131 and the downstream one 132, can be connected one with the other, at prefixed distances, with transversal connections made 23 with other strips of the same package,

in order to create separate blocks in the intermediate zone 121 of the central core. The blocks can be monitored and drained individually, thus allowing to detect with greater accuracy any leakage or inefficiency of the waterproofing system.

5.

The above-mentioned double-package system allows the following advantages:

10. 1) it creates a continuous artificial double waterproofing barrier, in flexible synthetic material, which again extends from the foundation up to the crest. The waterproofing barrier thus created can be extended to reach the deep layers of the ground by means of a screen obtained by grouting with suitable material, or by a plastic diaphragm, based on concrete-bentonite mixtures, starting from the foundation beam 16. Moreover, the upstream barrier consisting of the first waterproofing package 131 grants the required watertightness, while the second waterproofing package 132, downstream, constitutes a safety barrier;
20. 2) it creates a waterproofing barrier capable of following the deformations of the dam body which occur over time and due to the hydrostatic load, maintaining the waterproofing and deformability characteristics unaltered;
25. 3) it allows to test the efficiency of the waterproofing system by means of the monitoring system placed downstream of both packages, by means of a pipe system 17 which collects any infiltration or leakage downstream of the second package 132, as well as by means of a second system of pipes 22 which open towards the gap delimited by the two packages 131 and 132, in order to collect the
- 30.

5. since beam 16 would be in an accessible position, instead of being confined under the central core. It is also possible to further extend package 13 or 131 upstream, inside the reservoir created by the dam, by eliminating in this case the construction of the perimeter beam 16 on the upstream toe.

10. A further constructional alternative of the central core and of the waterproofing geomembranes is shown by the examples of figures from 11 to 14. In particular, with reference to figure 14, in this case the two packages 131 and 132 are executed by a plurality of inclined strips having the typical disposition of a "Christmas tree", that is to say with the strips of each package placed inclined alternatively in opposite directions, suitably heat-welded
15. along their longitudinal edges.

20. More precisely, both packages 131 and 132 have been executed by means of a plurality of heat-welded strips 25.1 - 25.n and 26.1 - 26.n, alternatively inclined upstream and downstream with the natural friction angle of the loose material used (normally between 15° and 40° in respect to a horizontal plan) according to the characteristics of the materials employed, and to the thickness of the layers of loose material A and B which constitute body 11A, 11'A of the dam and the various sections 121, 122 and 123 of
25. selected fill, constituting the central core, or in function of other circumstances or necessities.

30. Also in this case the characteristics of the loose material used for the various layers of the various sections of the central core can be the same or different, depending on the specific requirements.

Various constructive techniques are possible depending on

In particular figure 8 shows a possible type of realisation of extractable formworks 27, substantially consisting of two lateral walls 28, 29 parallelly placed and kept apart by means of upper crosspieces 30 and criss-crossed bars 31.

5. Number 32 indicates two hooking structures for hoisting formworks 27 by means of arm 33 of a crane, or by means of any other suitable hoisting device. The distance between the two lateral walls 28, 29 of the formworks substantially corresponds to the width of the intermediate area 121 of

10. the central core, included between the two packages 131 and 132.

The fundamental construction phases which characterise this first method are illustrated in figures 9 and 10 which represent intermediate moments in the construction of the

15. central core and of the dam body.

According to this first constructional technique, the elements of formworks 27 are placed side by side, aligned with the longitudinal axis of the dam, till they cover the whole length of the section interested. In these conditions

20. the geomembrane strips contained in packages 131 and 132 are placed on both sides of the formworks and laterally folded towards the outside. The geomembranes are then laid on formworks 27 with the interposition of a geotextile layer on both sides. The upper part of the two geomembrane

25. strips with the geotextiles are fastened at tops with temporary anchors, for example with clamps or other. The geomembranes, supplied in rolls, are heat-joined one to the other in order to get a total length equivalent to the total length of the various elements of the formworks which

30. are positioned along the longitudinal axis of the dam body to be executed. If needed, it is possible to create transverse compartmentation sectors 23 of the intermediate area of the central core, by transversally interposing

- between contiguous formworks, between the abutting faces, other geomembrane strips, protected by geotextiles, which are heat-coupled on the two edges to the upstream and downstream geomembrane strips positioned horizontally on the two sides of the central core.
- 5.

- The construction of the embankment can then start or continue. The first operation is the spreading and compacting by layers of the selected material of the central core 122 and 123, placed upstream and downstream of the formworks, and of the material of zone 121 placed inside the formworks in contact with the geotextile placed as a protection of the geomembrane on both faces.
- 10.

- Then the material with the biggest dimensions which constitutes body 11A, 11'A of the dam, upstream and downstream of the central core is laid and compacted. These operations continue until the dam body reaches an elevation close to the upper edge of the formworks which therefore result in the end embedded in the dam body.
- 15.

- The clamps which fasten the geomembranes and the geotextiles are removed, and the geomembranes with the geotextiles are folded again on the sides of formworks 27, as shown in figure 9. By means of a crane or other suitable hoisting device formworks 27 are removed for almost their whole height, if necessary, also by applying to it some vibrators which can favour the operation and contribute to compacting the material of the core. The formworks are then positioned for the execution of further layers of core 12 consisting of 121, 122 and 123, and of body 11A, 11'A of the dam. New geomembrane rolls are laid on the embankment, their edges overlapping on the ones of the geomembrane strips which have already been embedded in the central core under construction. The connection welds are executed, and
- 20.
- 25.
- 30.

- their watertightness is tested. The new geomembrane strips are then uplifted and fastened again over formworks 27, as shown with dashed lines in figure 10, always previously interposing the geotextile layers. The installation and
5. compaction of the selected material of the central core 12 and of the other inert materials of the dam body 11A, 11'A starts again according to the phases previously described, till the final elevation of the crest of the dam body is reached.
10. At last, a continuous concrete slab is built on the crest, and the upper edges of the two geomembrane 131 and 132, which have been thus executed and incorporated in the selected and injectable loose material of the central core, are mechanically fastened to it.
15. As an alternative to the above-described solution, which uses a plurality of formworks open along all the peripheral edges, the various horizontal strips of the geomembrane can be vertically fastened to a plurality of fixed or removable linear supports. The supports can consist of rigid pipes in
20. plastic material, which can be used also for any future injections or be of other type. The construction of the central core and of the dam body occurs substantially according to the same method adopted with the extractable formworks. The vertical supports, if removable, can be used
25. again as the elevation of the embankment increases, or can be left as permanent supports, embedded in the central core itself. If injection pipes are adopted as temporary support of the geomembranes, when construction is completed, and should injections be carried out inside the core to
30. waterproof it, the pipes themselves could be used for this purpose.

The constructional technique with the "zigzagged" or

"Christmas tree" geomembranes is shown in the following figures from 11 to 14, which represent some of the fundamental phases of this constructional technique.

5. The first strips of the two packages 131 and 132 are preliminarily fastened to the foundation beam 16 by means of proper watertight anchoring devices 34. The geomembranes are again supplied in rolls, joined one to the other in order to obtain a length equivalent to the total length of the core at the relevant elevation of the foundation; the
10. the two first strips of the geomembranes are folded towards the outside as in figure 11.

It is then possible to start the construction of the embankment; at first, a first layer of selected material constituting the intermediate zone 121 of the core, and the
15. two upstream and downstream layers of body 11A, 11'A of the dam, are laid down and compacted. Then the two geomembrane strips are folded inside, along the inclined sides of the layer of material 121, as described in figure 12.

Subsequently, two overlapped layers of selected material
20. are laid and compacted in the upstream zone 122 and in the downstream zone 123 of the central core, as it is schematically shown in figure 13.

Then the two following strips 131 and 132 are placed, with an inclination opposite to the previous ones, laying them
25. on the lateral layers 122 and 123, which have been previously laid and compacted, and joining them with the underlying strips.

The construction of the embankment and of the central core with the two "zigzag" or "Christmas tree" packages
30. continues in the same way in subsequent stages, as shown in

figure 14, till the final height of the embankment and of the central core, required for the dam body to be executed, are reached.

- During the construction of the central core and of the two
5. "Christmas tree" packages, vertical compartmentation sectors can be created by interposing, transversally to the longitudinal axis of the core, other geomembrane strips heat-coupled to the two upstream and downstream longitudinal geomembranes under construction. Also in this
10. case the various geomembrane strips are protected on both sides with geotextiles as in the previous case.

- Again, at the end a final crest is built, consisting of a continuous slab made of concrete or bituminous concrete or another suitable material, to which the upper edges of the
15. two packages are mechanically fastened.

- As mentioned several times, the material used for the waterproofing of the core is a geomembrane in synthetic, flexible, elastically yielding material, with a high thickness, for example with a thickness comprised between 2
20. mm and 4 mm, capable of resisting the high puncturing and abrasion stresses which can arise in correspondence of the contact interfaces with the loose material of the central core. The geomembrane is also capable of resisting the deformations - even concentrated - which the dam body can
25. undergo over time; therefore, the geomembrane must be made of a thermoplastic or elastomeric material able to allow even high elastic elongation. The junctions of the geomembrane strips can be executed with any suitable technique, for example by hot-air welding, keeping the
30. possibility of carrying out tests of the efficiency of the welds themselves.

barrier if needed, in localised areas or along the entire length and height of the central core.

- The described solutions guarantee very long durability. The use of geomembranes for waterproofing of the central core guarantees high reliability since geomembranes of this type have been operating for a great number of years on the facing of conventional dams. Accelerated ageing tests, carried out in the laboratory, have hypothesised a duration of the waterproofing material exceeding 500 years.
5. Furthermore, the geomembranes themselves, by being embedded in the central core, are protected from the action of the ultraviolet rays and from vandalism, and are therefore practically indestructible.
- 10.

Waterproofing layered membrane on the upstream face

15. With reference to the figures from 15 to 17, we will now describe a variant of the invention which allows the construction and waterproofing of embankment dams, including an exposed barrier on the upstream side, where a layered waterproofing membrane is laid and suitably anchored to the surface of the dam upstream face, so as to
20. allow the layered membrane to follow and/or adapt to any settlement movements of the dam thus constructed.

- Also in case of figures 15-17, the dam body 211 is executed with a suitable loose material, earth and/or rock, suitably placed by layers 212.1 - 212.n, superimposed and compacted.
- 25.

- In this case on the surface of the upstream face a waterproofing liner is provided, comprising a waterproofing package 213, whose composition is similar to the composition of waterproofing packages 13, 131, 132 of the previous examples. Therefore the waterproofing package 213
- 30.

consists of several adjoining bands or sheets 214, which extend in the direction of the slope of the upstream face, between the crest of the dam and the upstream foundation toe.

5. The single bands 214 of sheet material are unrolled and laid down on the upstream surface of the dam, and are fastened as they are placed to anchoring strips 215 in flexible synthetic material, suitably embedded between superimposed layers 212.1 - 212.n of the dam body.
10. The sheet material of the waterproofing package 213 is preferably a geocomposite including a layer of flexible and waterproofing synthetic material, coupled to a substrate of synthetic material having different properties. In particular the superficial layer, which will be in contact
15. with the water impounded in the reservoir of the dam, and therefore exposed also to the atmosphere, consists of a flexible synthetic geomembrane, impermeable and elastically yielding, for example in PVC, PP, PE or similar, while the underlying layer which will be in contact with the surface
20. of the dam, consists of a geotextile which performs the function of protective layer to avoid puncturing of the geomembrane, and at the same time supplies dimensional stability improving the friction coefficient of the composite geomembrane thus obtained.
25. Depending on the type of geotextile material adopted, and depending on the stony material and/or the characteristics of the material constituting the surface of the dam with which the geocomposite will be in contact, in general a natural friction angle is created, comprised between 25 and
30. 38 degrees. This means that depending on the slope of the upstream face of the dam, always included between the above-mentioned degrees, or inferior, during the

- installation of the waterproofing membrane the sheets of material 214, before being welded to the anchoring strips 215, remain stable and therefore do not slide, facilitating the installation. The waterproofing package 213 can also be
5. built so that the waterproofing geomembrane is independent from the geotextile which performs the function of protective layer. In this case the geotextile sheets are installed in contact with the upstream face of the dam, on which they are stable during installation, and the
10. waterproofing geomembrane is placed over the geotextile and anchored to sheets 215.

- As previously described, the single sheets of material 214 which compose the waterproofing package 213 must in any case be anchored to the dam body; should sheets 214 consist
15. of a geocomposite (waterproofing geomembrane coupled to the geotextile), the underlying layer geotextile co-operates in granting their stability and their resistance to sliding, to resist the actions due to waves and to wind in the part uncovered by water, and their resistance to loads due to
20. possible sediments or accidental loads which can affect the geomembrane, or to any underpressures which could be generated at the back side of package 213, in case of rapid dewatering of the reservoir.

- The anchorage of the single sheets of material 214 which
25. compose the waterproofing package 213 is made by means of strips 215. For this purpose, the anchoring strips 215 can be constituted with the same material which constitutes package 213, or with a synthetic material having similar chemical characteristics in order to allow welding by
30. thermo-fusion.

In particular, as shown in the example of figure 16, and in the detail of figure 17, the anchoring strips 215 are laid

between superimposed layers of the loose material constituting the dam body, during construction of the dam itself.

5. The anchoring strips 215 are placed parallel to the longitudinal axis of the dam and in such a way that the waterproofing synthetic material, which can be welded, faces the reservoir of the dam. The strips have a back side 215' which is placed on a substantially horizontal plan, firmly fastened between two superimposed layers 212' and
10. 212" of the stony material constituting the dam body. The anchoring strip 215 extends outside of the dam body with a front wing 215" which by gravity lies downwards in an L shape, against the external surface of the upstream face, in correspondence of the lower layer 212'. In alternative,
15. the same wing 215" can be folded upwards against the upper layer 212" after its construction.

- As shown in figure 16, the anchoring strips 215 are placed at different elevations, on several lines, maintaining an alternate or staggered disposition between the anchoring
20. strips of one line and the anchoring strips of the two contiguous lines, with interaxis or distances which can vary, and at different elevations, depending on each specific project.

25. The sheets of waterproofing material 214 rolled up in rolls are progressively laid starting from the crest, or from any intermediate elevation, towards the dam upstream toe, and during their unrolling they will progressively cover the anchoring strips 215 which have been embedded in the layers of loose material which form the dam body.

30. In correspondence of the overlapping of the sheets constituting package 213 with the wings 215" of the

- anchoring strips, part of the geotextile layer is removed or cut-out from each geocomposite sheet 214, creating a welding area 216, so that the back surface of the layer of synthetic material of the geomembrane, in the area 216
5. uncovered by the geotextile, is in contact with the front surface of wing 215", which is in a material chemically compatible, in order to allow the welding by thermo-fusion. In case the waterproofing geomembrane and the geotextile are independent, before the installation of sheets 214 it
10. will be necessary to remove the section of geotextile in correspondence of strips 215, in order to create the welding area 216.

- Welding can occur by points, by lines or on the whole surface of area 215" of the anchoring wing according to the
15. requirements of each project.

- As shown in figure 17, in a way similar to the previous examples, a transition and draining zone 217 is created between the waterproofing package 213 and the earthfill and/or rockfill, during the construction of the dam. Zone
20. 217 consists of gravel and/or material with a suitable grading, permeable to water for the drainage of any leakage, and injectable by sealing fluids.

- A second alternative for the fastening of the waterproofing membrane to the dam body is shown in figures 18 and 19 of
25. the drawings attached.

- As shown, also in this case the dam body is formed by superimposed layers 312' - 312", foreseeing during the construction of the dam the insertion of anchoring strips 315 to which the waterproofing membrane 313, perfectly
30. identical or similar to the one of the previous examples, is then welded.

- In case of figures 18 and 19, unlike in the previous example where the anchoring strips 215 were folded in an L shape downwards or upwards against the upstream face of the dam, in this case during the construction of the dam body by superimposed layers, the anchoring strips 315 are "C" folded, so that each anchoring strip 315 has a first extreme part 315' embedded in the material of one layer, a second extreme part 315" embedded between the material of the previous layer and the material of the following layer, and an intermediate part 315'" for welding the waterproofing membrane 313 which extends on the front surface of the dam body, between the two extreme parts 315' and 315" of the same anchoring strip.

- Also in this case, if the waterproofing membrane 313 is a geocomposite, the back geotextile layer shall be removed, while if the geotextile is independent it shall be removed in correspondence with strips 315, in order to create in any case a welding area 316, also providing between membrane 313 and the earth and/or rock layers of the dam body, a transition and drainage zone 317 in loose material with a fine grading, as in the previous case.

- In all cases, in order to obtain a higher protection degree for the membrane, a further protection layer consisting of a geotextile or similar can be optionally provided between the membrane and the transition and/or drainage zone 12, 122, 123, 212 and 312.

- In the previous examples, as shown in figure 16, a disposition parallel to the slope of the dam upstream face has been hypothesised for the sheets of material 214 which constitute the waterproofing membrane; yet, it is evident that the installation of the membrane, instead of by bands parallel to the slope, can be executed by horizontal bands,

- as schematically shown in figure 20, starting in this case from the dam upstream toe and proceeding towards the crest, and partially overlapping the horizontal edges of contiguous bands; in this way it is possible to partially exploit the dam during its construction. In alternative to what previously described, the anchoring strips 215 or 315, instead of creating distanced anchoring points, could be prolonged for part or for the whole length of the dam, practically creating continuous welding areas. Both in case of installation of sheets 214 parallel to the slope, and of installation by horizontal bands, loss of watertightness that should occur in the membrane, in damaged areas, can be repaired by welding elements of synthetic materials identical or compatible with the material of the membrane itself.
5. 10. 15.

- The advantage of the solutions with geomembrane on the upstream face consists in the fact that a continuous waterproofing liner, installed on the surface of the upstream face, prevents water from infiltrate into the upstream part of the dam body.
- 20.

Perimeter anchorage

- In all cases suitable anchoring devices of the waterproofing membrane shall be provided in correspondence of the upstream toe and of the crest of the dam.
25. 30. At crest, the waterproofing membrane can be, for example, embedded in a trench where the edge of the membrane is laid down and suitably ballasted with gravel or other material, or can be anchored by a mechanical anchorage whenever there is a concrete structure, for example a road curb, a parapet wall or other structure which normally constitutes the upper finishing of the dam.

The fastening of the membrane to the upstream toe of the dam and along the whole periphery, in case of figures from 15 to 20 can be executed in any way which is adequate to grant a continuity of the waterproofing barrier towards the underlying ground, for example as shown in figure 15 and in the detail of figure 21.

In this case the execution of a concrete perimeter plinth 400 is foreseen, to which the lower edge of the waterproofing membrane 213 is watertight anchored, by folding it forward and against the upper surface of plinth 400, if necessary regularised by means of suitable resins, to which the edge of the membrane itself is fastened by means of a metal profile 401 which compresses membrane 213 against plinth 400 with the interposition of a gasket strip 402 and/or of a regularisation layer 405; profile 401 is anchored to plinth 400 by means of a plurality of threaded rods 403 partially embedded or secured in the concrete of the plinth, on which fastening nuts 404 are screwed. Another way of anchoring the membrane to plinth 400 can be an "insert" type anchorage: a slot is created in plinth 400 into which the membrane is inserted and then watertight anchored by embedment in proper waterproofing substances such as epoxy resins or similar.

The anchorage of the membrane to plinth 400 also allows to execute grouting of proper fluid substances for the creation of a waterproofing screen which prevents water from entering between plinth 400 and the contact surface with the foundation ground, in a way similar to the case of figure 3.

The anchorage to plinth 400 provides a soft connection of the membrane between the dam body and the base plinth, as illustrated in figure 21.

For this purpose, the lower edge of membrane 213 is folded to create a bend 220 along a trench 221 executed between the inside edge of plinth 400 and the transition zone 217.

5. The advantage of this solution is that in case settlements occur in the dam body, bend 220 allows the membrane 213 to deform following the movements of the dam body, creating an elongation compatible with the mechanical resistance of the membrane itself. If so required, it is also possible to create a layer of anti-grip material and provide a layer of protective geotextile along the trench for creation of the bend, between membrane 213 and zone 217.
- 10.

- Should the waterproofing membrane be ballasted with a covering element 222, as schematically shown in figure 21, trench 221 can be filled with a layer of loose material with a very fine grading, for example sand, which does not oppose a substantial resistance to the movement of membrane 213 in case it is subjected to tensile stress due to movement and/or settlements of the dam body. The filling layer will be a protection for membrane 213 from any mechanical action by ballast 222. If needed, it is also possible to create a layer of anti-grip material and provide a layer of protection geotextile, along the trench for creation of the bend, between membrane 213 and area 221.
- 15.
- 20.

25. The advantage of using a geocomposite consists in the fact that the geotextile substrate, if coupled adherent to the PVC waterproofing layer or other proper elastically deformable synthetic material, supplies an increase in the mechanical resistance of the geocomposite itself.
30. Therefore, in the event that significant deformations are caused in the geocomposite, normally in the range of 10-20%, the geotextile substrate which is heat-welded to the

- PVC layer or similar layer, is detached from it, allowing the two layers to become independent. Therefore, due to the strong friction, the geotextile will remain adherent to the diaphragm consisting of the layer of transition material in the dam body, while the elastic PVC geomembrane or similar, having an elongation coefficient which is significantly higher and which can reach values as high as 300%, will be able to move freely on the underlying geotextile and to therefore contribute with a larger surface to the distribution of the stresses.
- 5.
- 10.

- However, it is clear that what has been said and shown with reference to the attached drawings has been given as an exemplification and illustration of the general principles of the invention, and of some of its preferential configurations, and that it is intended that other modifications and alternatives are possible both to the structure of the dam, to the structure of the transition core and/or of the waterproofing membrane, and in the construction techniques, without departing from what is being claimed.
- 15.
- 20.

CLAIMS

1. A method for the construction and the waterproofing of dams comprising an embankment body (11) having a longitudinal axis, in which the dam body (11) is made by superimposed layers of coarse loose material (A) such as earth and/or rock, and a water barrier (12) provided by a waterproofing core which develops from the bottom to the top and which extends along the longitudinal axis of the dam body (11), characterised by the steps of providing a water barrier (12) including at least one synthetic and elastically yieldable waterproofing membrane (13) and at least one transition zone (B) of selected fine loose material having a high permeability to water and suitable for injecting fluid sealing substances; providing said transition zone (B) between one side of the waterproofing membrane (13) and the dam body (11) during the layered construction of the dam body itself (11), and anchoring the waterproofing membrane (13) to the dam body.

2. A method according to claim 1, characterised by providing a supporting substrate (15) in synthetic material, of the geotextile type, coupled to the waterproofing membrane (13) on the side of the membrane (13) facing towards the transition zone (B).

3. A method according to claim 2, characterised by providing an additional substrate in synthetic material, of the geotextile type, between the supporting substrate (15) of the waterproofing membrane (13) and the body (11) of the dam.

4. A method according to claims 2 or 3, characterised by the fact that the supporting substrate (15) of the waterproofing membrane (13) and the additional substrate

are made of geotextile.

5. A method according to claim 1, characterised by anchoring the waterproofing membrane (13) by strips (215) of synthetic material, chemically compatible and heat-weldable to the waterproofing membrane (13), partially embedded and secured into the loose material of the transition zone (B) of the water barrier (12) and/or of the dam body (11).

10. 6. A method according to claim 1, characterised by the fact that the water barrier (12) comprises a core member inside the dam body (11).

15. 7. A method according to claim 1, characterised by the fact that the water barrier comprises a waterproofing membrane (213) in correspondence of the upstream face of the dam body (211).

20. 8. A method according to claim 7, characterised by the fact of anchoring the waterproofing membrane (213) by strips (215) of synthetic material, chemically compatible with and heat-weldable to the waterproofing membrane (213), said strips (215) being partially embedded into the loose material of the dam body, and having an anchoring wing (216) for the membrane (213), folded against the upstream face of the dam (211).

25. 9. A method according to claim 7, characterised by anchoring the waterproofing membrane (313) by C-folded strips (315) of synthetic material, chemically compatible with and heat-weldable to the membrane (313), said C-folded strips (313) having the end parts embedded in the loose material of the dam body (11), and comprising an
30. intermediate anchoring portion (316) for the membrane (313)

which extends against the upstream face of the dam (311).

5. 10. A method according to claim 1, characterised by performing on at least one side of the water barrier (12, 212, 312), a permeable and injectable zone (B) of fine loose material having a permeability and injectability comprised between 1×10^{-1} and 1×10^{-5} cm/sec.

10. 11. A method according to claims 1 and 7, characterised by performing a freely deforming bent portion along the bottom edge of the membrane (213), next to anchoring devices (401) along said bottom edge.

12. A method according to claim 11, characterised by protecting the bent portion at the bottom edge of the membrane (213) by a layer of fine loose material (220).

15. 13. A method according to claim 12, characterised by providing a substrate of synthetic material, of the geotextile type, to protect the waterproofing membrane (213), between the same membrane (213) and a layer of ballasting material (221).

20. 14. A method according to claim 13, characterised by providing an anti-grip material between the protection synthetic material and the layer of ballasting material (221).

25. 15. A method according to claims 7 or 8, characterised by providing anchoring strips (315) for the membrane (313) staggered along horizontal lines parallelly arranged to the longitudinal axis of the dam (311).

16. A method according to claims 7 or 8, characterised by providing continuous anchoring strips (215) along

horizontal lines, parallelly arranged to the longitudinal axis, for a part or for the whole length of the dam (211).

5. 17. A method according to claim 7 in which the membrane (213) comprises a plurality of bands (214) of sheet material, characterised by constructing the waterproofing membrane (213) by positioning bands (214) side by side arranged extending and in the direction of the slope of the upstream face of the dam (211).

10. 18. A method according to claim 7 in which the membrane (213) comprises a plurality of bands (214) of sheet material, characterised by constructing the waterproofing membrane (313) by positioning bands side by side and horizontally extended in the direction of the axis of the dam.

15. 19. A method according to claim 18, characterised in that the membrane (313) is constructed starting from a foundation of the dam (311), allowing a partial exploitation of the dam itself during its construction.

20. 20. A method according to claim 1, characterised by embedding a waterproofing membrane of the water barrier (12) into a core in fine loose material, inside the dam body (11).

25. 21. A method according to claim 1, characterised by performing the water barrier (12) in a central position of the dam body (11), by disposing two waterproofing membranes (13) parallelly arranged and spaced apart in respect to the longitudinal axis of the dam (11), providing a core of fine loose material to define an intermediate zone between the two membranes (13), suitable for injecting a sealing fluid
30. to repair loss of impermeability that should occur in the

membrane (13) on the upstream side of the dam (11).

5. 22. A method according to claim 7, characterised by welding pieces of synthetic material to repair loss of impermeability in a damaged part of the waterproofing membrane (13).

10. 23. Embankment dam for impoundment of water in a reservoir, constructed according to the method of claim 1, the dam comprising a body (11) of an earthfill and/or rockfill loose material, and a central waterproofing barrier (12), characterised in that the central barrier (12) of the dam (11) comprises at least one waterproofing membrane (13) in elastically yieldable synthetic material, parallelly positioned to a longitudinal axis of the body (11) of the dam, and at least one lateral transition zone (B) in selected fine loose material, having a high degree of injectability and permeability on each side of the membrane (13).

20. 24. Embankment dam according to claim 23, characterised in that at least one protection layer in flexible synthetic material is disposed between each side of the waterproofing membrane (13) and the selected loose material of the lateral transition zone (B).

25. 25. Embankment dam according to the previous claims, characterised in that the waterproofing membrane (13) comprises a layer in thermoplastic sheet material coupled to a supporting substrate of geotextile, on at least one side thereof.

30. 26. Embankment dam according to claim 23, characterised in that the waterproofing membrane (13) is watertight fastened to an anchoring beam (16) provided

parallel to the longitudinal axis and along the bottom perimeter of the body (11) of the dam.

5. 27. Embankment dam according to claim 23, characterised in that the anchoring beam (16) is parallelly arranged to the upstream toe of the dam body (11), and in that the waterproofing membrane (13) extends under the dam body (11), towards the aforementioned anchoring beam (16).

10. 28. Embankment dam according to claim 23, characterised by comprising a draining and monitoring pipe system for water seeping through the central waterproofing barrier (12) of the dam.

15. 29. Embankment dam according to claim 23, including a rigid structure (10), characterised in that the waterproofing membrane (13) is watertight connected to the rigid structure (10) of the dam by at least one freely deformable waterproofing strip (18').

20. 30. Embankment dam according to claim 29, characterised in that the waterproofing strip (18') connecting the waterproofing membrane (13) to the rigid structure (10) of the dam is shaped so as to form a set of bellows.

25. 31. Embankment dam according to claim 23 and to one or more following claims, characterised in that the water barrier (12) comprises a first and a second waterproofing membrane (131, 132) laterally spaced one from the other, and a central transition zone (C), in selected fine loose material, between the two membranes (131, 132), as well as a transition side zone (B) in selected fine loose material, on each side of the waterproofing membranes (131, 132)
30. opposite to the central transition zone (C).

32. Embankment dam according to claim 31, characterised by the fact that the two waterproofing membranes (131, 132), extend parallel to the longitudinal axis of the dam.

5. 33. Embankment dam according to claim 31, characterised in that the waterproofing membranes comprise a number of longitudinal strips (25n) which are alternatively inclined on the opposite sides of each lateral transition zone (B).

10. 34. Embankment dam according to claim 31, characterised in that the transition zone (C) between the two waterproofing membranes (131, 132) and the transition side zone (B) are connected to respective drainage and monitoring pipe system for water seeping through the loose
15. selected material of the transition zones (B, C).

35. Embankment dam according to claim 31, characterised by comprising at least one transverse partition in waterproofing material (23), watertightly welded between the two membranes (131, 132) of the
20. waterproofing barrier (12) of the dam.

36. Embankment dam according to claim 31, characterised in that the transition zone (C) between the two membranes (131, 132) comprises selected loose material having an injectability and waterproofing degree different
25. from the selected loose material of the two transition side zones (B).

37. Embankment dam according to any previous claim, characterised in that the waterproofing barrier (12) comprises selected loose material having a injectability
30. and waterproofing degree comprised between 1×10^{-1} and 1×10^{-2}

cm/s.

5. 38. Embankment dam according to any previous claim, characterised in that the selected loose material of the waterproofing barrier (132) is grouted with sealing fluid substances in correspondence of localised water seepage areas through failures of the membranes (131, 132), either for the whole length of the waterproofing barrier (112), or in correspondence of areas of its intermediate transition zone (B), between the aforementioned transverse partitions (23).
- 10.

39. Embankment dam according to any previous claim, characterised by including injection pipes for waterproofing substances, provided before or after the construction of the waterproofing barrier (12) of the dam.

15. 40. Embankment dam constructed according to the method of claim 1, of the type comprising an earthfill and/or rockfill body (11) and a waterproofing barrier, characterised in that the waterproofing barrier includes a waterproofing membrane (213, 313) in elastically yieldable synthetic material, positioned parallel to the longitudinal axis of the body of the dam, and a transition zone (217) in selected loose material having a high injectability and permeability degree, between the waterproofing membrane (213, 313) and the upstream surface of the dam body; and in that anchoring devices (215, 315) are provided for the waterproofing membrane (213, 313) comprising a number of anchoring strips of a synthetic material, chemically compatible and heat-weldable to the waterproofing membrane (213, 313), said anchoring strips (215, 315) partially extending from the upstream face of the dam body (11) and partially being embedded in the loose material of the waterproofing barrier (12) and of the dam body (11).
- 20.
- 25.
- 30.

41. Embankment dam according to claim 40, characterised in that the anchoring strips (215, 315) for the membrane (213, 313) are positioned along parallel rows, on the upstream face of the dam body (11).

5. 42. Embankment dam according to claim 41, characterised in that the anchoring strips (215, 315) of each row are staggered in respect to the anchoring strips of a contiguous rows of strips.

10. 43. Embankment dam according to claim 41, characterised in that at least one protection substrate, in synthetic material, is disposed between the waterproofing membrane (213, 313) and the zone (217) in loose material of the dam body.

15. 44. Embankment dam according to claim 41, characterised by the fact that the waterproofing membrane (213) is made by waterproofing bands (214), arranged side by side and positioned parallel to the slope of the upstream face of the dam.

20. 45. Embankment dam according to claim 41, characterised by the fact that the waterproofing membrane (313) is made by waterproofing bands, arranged horizontally side by side and positioned parallel to the longitudinal axis and from the bottom of the dam.

25. 46. Embankment dam according to claim 41, characterised in that the waterproofing membrane (213) is folded to create a freely extensible portion along its lower edge.

47. Embankment dam according to claim 46,

characterised in that a loose ballasting material (221) is placed over the lower folded portion of the waterproofing membrane (213).

5. 48. Embankment dam according to claim 47, characterised in that a protection layer in synthetic material is disposed between the ballasting material (221) and the folded portion of the membrane (213).

10. 49. Embankment dam according to claim 47, characterised in that a layer of anti-grip material is disposed between the ballasting material (221) and the synthetic protection layer of the membrane (213).

15. 50. Embankment dam according to claim 41, characterised in that the lower edge of the waterproofing membrane (213) is watertight mechanically fastened to a base plinth (400) along the bottom perimeter of the body (11) of the dam.

20. 51. Embankment dam according to claim 41, characterised in that the lower edge of the waterproofing membrane (213) is fastened, by watertight insertion, to a base plinth (400) along the bottom perimeter of the body (11) of the dam.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 11




Fig. 12




Fig. 13






Fig. 14






Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 E02B3/10 E02D17/18 E02D19/18

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E02B E02D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|---|---|
| X | DE 44 02 862 A (HABERL MICHAEL) 16 June 1994 (1994-06-16) the whole document | 1,2,6,7, 10,20, 21, 23-25, 32,40, 43,50 |
| A | DE 38 08 269 A (SAARLAEND GRUBENAUSSAU) 21 September 1989 (1989-09-21) column 3, line 31 -column 4, line 45; figures 1-8 — -/- | 1,6,7, 10,17, 18,20, 23,26, 40,43, 50,51 |

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"B" document member of the same patent family

Date of the actual completion of the international search

30 March 2000

Date of mailing of the international search report

06/04/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3010

Authorized officer

Tellefsen, J

INTERNATIONAL SEARCH REPORT

Patent Application No.

PCT/EP 99/09534

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|--|-------------------------------------|
| A | US 5 454 668 A (LIAO ANDREW) 3 October 1995 (1995-10-03) the whole document | 1,23,40 |
| A | US 4 266 885 A (NAITO KAZUAKI ET AL) 12 May 1981 (1981-05-12) column 3, line 28 -column 9, line 16; figures 1-9 | 1,23,40 |
| A | US 3 811 286 A (FEINER A) 21 May 1974 (1974-05-21) column 1, line 58 -column 6, line 44; figures 1,2 | 1,6-8, 14,19, 20,23, 40,51 |

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/09534

| Patent document cited in search report | | Publication date | Patent family member(s) | Publication date |
|---|---|---------------------|----------------------------|---------------------|
| DE 4402862 | A | 16-06-1994 | NONE | |
| DE 3808269 | A | 21-09-1989 | NONE | |
| US 5454668 | A | 03-10-1995 | AU 690263 B | 23-04-1998 |
| | | | AU 2296395 A | 18-12-1995 |
| | | | AU 7747998 A | 01-10-1998 |
| | | | GB 2302357 A, B | 15-01-1997 |
| | | | WO 9532339 A | 30-11-1995 |
| | | | US 5609438 A | 11-03-1997 |
| US 4266885 | A | 12-05-1981 | NONE | |
| US 3811286 | A | 21-05-1974 | DE 2160874 A | 14-06-1973 |
| | | | CA 960047 A | 31-12-1974 |
| | | | CH 563502 A | 30-06-1975 |
| | | | ES 404342 A | 01-06-1975 |
| | | | FR 2164151 A | 27-07-1973 |
| | | | GB 1376225 A | 04-12-1974 |
| | | | IT 956521 B | 10-10-1973 |
| | | | JP 996917 C | 20-05-1980 |
| | | | JP 48064729 A | 07-09-1973 |
| | | | JP 54031627 B | 08-10-1979 |

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.